

DECLARATION OF PERFORMANCE

n° PROFR013/a

Date : June, 30th 2013

1 - *Unique identification code of the product-type:*

PROFR013

2 - *Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :*

SOPRATUILE QUEUE DE CASTOR

3 - *Intended use (or uses) of the construction product :*

Bitumen shingles with mineral and/or synthetic reinforcements

4 - *Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :*

**SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG
www.soprema.com**

5 - *Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :*

Non applicable

6 - *System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :*

AVCP 3

7 - *Case of the declaration of performance concerning a construction product covered by a harmonised standard :*

The CSI (Notified Body n° 0497) :

- **made the determination of the product-type on the basis of type testing, according to system 3**
- **issued the corresponding tests reports.**

8 - *Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :*

Non applicable

**SOPREMA**

Roofing material solutions

DECLARATION OF PERFORMANCE

n° PROFR013/a**Date : June, 30th 2013***9 – Declared performances :*

| Essential characteristics | Performances | Harmonised Technical Specification |
|---|---|---|
| Mechanical properties Tensile strength (N / 50 mm) Width Height | > 850 > 510 | EN 544 : 2011 |
| Resistance to tearing (N) | > 120 | |
| Reaction to fire | E | |
| External fire performance (Note 1) | F_{ROOF} (t1,t2,t3,t4) | |
| Mass of bitumen (g/m ²) | ≥ 1300 | |
| Dimensional variation (mm) | ≤ ± 3 | |
| Durability of mechanical strength | Conform | |
| Durability for water permeability: Flow resistance at elevated temperature (mm) Adhesion of mineral granules or slate chippings (g) Water absorption (%) | < 1 < 0,5 < 1 | |

Note 1 : Since external fire performance depends on the other components of the roof build-up, no performance can be given.

*10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.**This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.**Signed for and on behalf of the manufacturer by :***Strasbourg,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**