

DECLARATION OF PERFORMANCE

n° PROFR012/a

Date : June, 30th 2013

1 – *Unique identification code of the product-type:*

PROFR012

2 – *Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :*

SOPRATUILE

3 – *Intended use (or uses) of the construction product :*

Bitumen shingles with mineral and/or synthetic reinforcements

4 – *Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :*

**SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG
www.soprema.com**

5 – *Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :*

Non applicable

6 – *System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :*

AVCP 3

7 – *Case of the declaration of performance concerning a construction product covered by a harmonised standard :*

The CSI (Notified Body n° 0497) :

- **made the determination of the product-type on the basis of type testing, according to system 3**
- **issued the corresponding tests reports.**

8 – *Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :*

Non applicable

**SOPREMA**

Roofing material solutions

DECLARATION OF PERFORMANCE

n° PROFR012/a**Date : June, 30th 2013***9 – Declared performances :*

Essential characteristics	Performances	Harmonised Technical Specification
Mechanical properties Tensile strength (N / 50 mm) Width Height	> 850 > 510	EN 544 : 2011
Resistance to tearing (N)	> 120	
Reaction to fire	E	
External fire performance (Note 1)	F_{ROOF} (t1,t2,t3,t4)	
Mass of bitumen (g/m ²)	≥ 1300	
Dimensional variation (mm)	≤ ± 3	
Durability of mechanical strength	Conform	
Durability for water permeability: Flow resistance at elevated temperature (mm) Adhesion of mineral granules or slate chippings (g) Water absorption (%)	< 1 < 0,5 < 1	

Note 1 : Since external fire performance depends on the other components of the roof build-up, no performance can be given.

10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.

This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

**Strasbourg,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**