

DECLARATION OF PERFORMANCE

n° WPBEX102

Date : June, 30th 2013

1 - *Unique identification code of the product-type:*

WPBEX102

2 - *Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :*

SOPRAVAP STICK TS

3 - *Intended use (or uses) of the construction product :*

Flexible sheets for waterproofing – Bitumen water vapour control layer

4 - *Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :*

**SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG
www.soprema.com**

5 - *Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :*

Non applicable

6 - *System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :*

AVCP 3

7 - *Case of the declaration of performance concerning a construction product covered by a harmonised standard :*

The LNE (Notified Body n°0071):

- **made the determination of the product-type on the basis of type testing, according to system 3**
- **issued the corresponding tests reports.**

8 - *Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :*

Non applicable

DECLARATION OF PERFORMANCE

n° WPBEX102

Date : June, 30th 2013

9 – Declared performances :

Essential characteristics	Performances	Harmonised Technical Specification
Reaction to fire	E	EN 13970:2004
Watertightness	Conform	
Tensile properties : Tensile strength L x T (N / 50 mm) Elongation L x T (%)	≥ 600 x 600 2 x 2	
Resistance to impact (mm)	600	
Shear resistance of joints (N/50 mm)	≥ 600	
Flexibility at low temperature	-16°C	
Resistance to tearing (N)	≥ 150	
Durability (resistance to humidity) Against artificial ageing Against chemicals	Conform NPD	
Properties of water vapour transmission (resistance to humidity)	≥ 6,8 10⁴	
Dangerous substances (Notes 1 and 2)	Complies	

Note 1 : This product does not contain asbestos or tar constituents.

Note 2 : Since there is no European test method available, no performance declaration for leaching behavior can be made. It must be made according to national rules in force in the place of use.

10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.

This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

**Strasbourg,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**

