

# ALSAN<sup>®</sup> 500 F



## 1 PRESENTATION

**ALSAN<sup>®</sup> 500 F** is a single-component, ready-to-use UV resistant watertight aliphatic polyurethane resin, accessible by pedestrians.

**ALSAN<sup>®</sup> 500 F has CE marking according to European Technical Approvals.**

## 2 CHARACTERISTICS

In compliance with current standards or internal standards.

	<b>ALSAN<sup>®</sup> 500 F</b>
<b>Physical state</b>	Semi-fluid paste, shiny appearance once dry.
<b>Standard colours*</b>	RAL 1001 (beige) RAL 1014 (ivory) RAL 7032 (pebble grey) RAL 7040 (window grey) *More colours available on request
<b>Wet mass density at 25°C</b>	1130 kg/m <sup>3</sup> ( ± 50)
<b>Viscosity</b>	25 Po ( ± 10)
<b>Solid content (by weight)</b>	77 % ( ± 5)
<b>Flash point</b>	> 21°C
<b>Flammability</b>	Easily flammable
<b>Drying time</b>	12 to 48 hours depending on temperature Accessible after 72 hours
<b>Classification AFNOR NF T 36-055</b>	Family I, Class 6a

Viscosity is given for informative purposes, being a single component, it may tend to evolve.

## 3 PACKAGING AND CONSUMPTION

Cans: 5 kg and 25 kg.

Storage: 6 months in original, unopened container, turned upside-down and kept away from heat. Storage temperature >5°C.

Approximate consumption: 1 layer of 300 g/m<sup>2</sup>



## 4 USER'S APPLICATION

**ALSAN® 500 F** is a coloured finishing layer for **ALSAN® 500** Liquid Waterproofing System procedure to be used without additional protection.

**ALSAN® 500 F** is used in the **ALSAN® 500** waterproofing kit, which conforms to **European Technical Approvals ETA-07/0111**, confirmed by the **CE marking**.

**ALSAN® 500 F** provides stronger weight resistance and makes cleaning easier.

For new work and renovation.

## 5 INSTALLATION

Product must be applied with a brush or roller according to technical instructions.

Product must be well mixed in order to obtain a proper homogenisation of components.

Product cleaning: **Diluant V** or **Diluant L** (thinners).

## 6 SPECIAL INDICATIONS

### Hygiene, health and environment:

- Flammable: ensure that all cans, empty or full, of flammable substances are at least 10 m away.
- Contains isocyanates. When using, do not smoke, drink or eat. Refer to instructions.
- Do not breathe in fumes and avoid skin contact.
- In case of ingestion, do not make the subject vomit: immediately consult a specialist and produce the package of substance.
- Keep product away from any flames or sparks – do not smoke.
- Only use in well-ventilated areas.

For more information, please refer to the relevant Safety data Sheet.

### Quality control:

**SOPREMA** has always attached the highest importance to Quality Control. For this reason, we operate an internationally recognized Quality System according to **ISO 9001: 2008** with the system being independently monitored and certified by **BSI**.

