

# **DECLARATION OF PERFORMANCE**

**n° PROFR003/a**

**Date : June, 30<sup>th</sup> 2013**

*1 – Unique identification code of the product-type:*

**PROFR003**

*2 – Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :*

**STRATHERM**

*3 – Intended use (or uses) of the construction product :*

**Underlays for discontinuous roofing  
Underlays for wall**

*4 – Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :*

**SOPREMA SAS  
14, rue de Saint-Nazaire – CS 60121  
67100 STRASBOURG  
www.soprema.com**

*5 – Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :*

**Non applicable**

*6 – System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :*

**AVCP 3**

*7 – Case of the declaration of performance concerning a construction product covered by a harmonised standard :*

**The LNE (Notified Body n°0071):**

- **made the determination of the product-type on the basis of type testing, according to system 3**
- **issued the corresponding tests reports.**

*8 – Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :*

**Non applicable**

## **DECLARATION OF PERFORMANCE**

**n° PROFR003/a**

**Date : June, 30<sup>th</sup> 2013**

*9 – Declared performances :*

<b>Essential characteristics</b>	<b>Performances</b>	<b>Harmonised Technical Specification</b>
Reaction to fire	<b>F</b>	<b>EN 13859-1 : 2010 EN 13859-2 : 2010</b>
Resistance to water penetration	<b>W1</b>	
Tensile properties :		
Tensile strength - Longitudinal - Transversal	<b>450 ± 50 N/50 mm 400 ± 70 N/50 mm</b>	
Elongation - Longitudinal - Transversal	<b>40 ± 5 % 30 ± 5 %</b>	
Resistance to tearing (Nail shank) - Longitudinal - Transversal	<b>300 ± 50 N 300 ± 50 N</b>	
Flexibility at low temperature (Pliability)	<b>-40°C</b>	
Artificial ageing behavior :		
Resistance to water penetration Tensile strength - Longitudinal - Transversal	<b>W1 410 ± 50 N/50 mm 380 ± 50 N/50 mm</b>	
Elongation - Longitudinal - Transversal	<b>35 ± 5 % 30 ± 5 %</b>	
Water vapour transmission properties (Sd)	<b>0,05 [-0,03 ; +0,04] m</b>	<b>EN 13859-2 : 2010</b>

*10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.*

*This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.*

*Signed for and on behalf of the manufacturer by :*

**Strasbourg,  
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**

