



- For sealing inside and outside, for rendering and can be painted over
- Humidity-regulating with variable Sd value
- Suitable for renovation and new builds

Packaging

	Box weight [kg]	Roll length [m]	Roll width [mm]	Box contents [units]
PAVAFIX WIN	4,0	25	90	4

Characteristics

Material	PET fleece and PA foil
Thickness [mm]	0,65
Minimum installation temperature for base and air [°C]	frozen over, air -5
Installation temperature tape [°C]	-5 to +40
Temperature resistance [°C]	-40 to +80
For rendering	yes
Resistance to water penetration	W1
UV weathering stability	3 months

Product description

For sealing connection joints in windows, doors and interior construction panel PAVAROOM to the adjacent building part. The humidityregulating tape can be used for interior and exterior sealing, and so avoids installation errors. The joint remains dry all year round, so damage from condensation can be effectively prevented. With its high-performance adhesive surface, the tape is suitable for applying directly to the frame and the adjacent smooth masonry. Always consult the local regulations and installation guidelines of the manufacturer.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements. For more information, please refer to the relevant safety data sheet.

Storage

Store cool and dry, protected from sunlight.