

GEOTEXTILE 200

Description

GEOTEXTILE 200 is a non woven polyester fleece.

Composition & packing

Composition	non woven polyester
Mass (g/m ²)	200
Dimensions of the roll (m)	100 x 2,2
Mass of the roll (kg)	44

Store in a horizontal position in a dry place, protected against moisture and sunlight.

Characteristics

Membrane thickness at 2 kPa (mm) (EN 9863-1)	MDV	1,7
Tensile force L (N/m) (EN 10319)	MDV	2760
Tensile force T (N/m) (EN 10319)	MDV	3800
Elongation at rupture L (%) (EN 10319)	MDV	35
Elongation at rupture T (%) (EN 10319)	MDV	45
Resistance to static puncture (N) (EN 12236)	MDV	600
Resistance to impact (mm) (EN 13433)	MDV	35

MDV = manufacturer declared value / MLV = manufacturer limiting value / NPD = no performance determined

GEOTEXTILE 200 is rot and bitumen resistant and has a high resistance against bacterial deterioration.

Installation

GEOTEXTILE 200 can be used as a compression-, separation- or protection layer on most supports.

To prevent deterioration it needs to be completely covered after installation (It can't be applied when permanently exposed to UV radiation).

Special indications

Hygiene, Health and Environment

The product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.