



- Economic reinforcement board for timber frame construction
- +/- 25 % less fixation points in relation to a 125 cm width board
- The sealing of the joints between the boards with PAVAFIX WIN guarantees a high airtightness

Packaging

Thickness [mm]	Boards/pallet	Dimensions [mm]	m ² /pallet [m ²]	Mass/pallet [kg]	Thermal resistance (R _d) [m ² .K/W]
8	25	2820 X 1872	132,0	1076	0,05

Characteristics

Density [kg/m ³]	1000
Thermal conductivity (λ _d) (EN 13171) [W/(m.K)]	0,140
Specific heat capacity (c) [J/(kg.K)]	2100
Water vapour diffusion resistance coefficient (μ) [-]	185
Reaction to fire (EN 13501-1)	D-s1, d0
Waste code according to The European Waste Catalogue (EWC)	030105; 170201
Edge profile	straight

Product description

PAVAPLAN is a natural and ecological, airtight and vapour-permeable reinforcement board based on wood fiber.

PAVAPLAN is suitable for indoor climate class 2 such as bathrooms and kitchens.

The vapour-diffusion-open character of the board contributes in combination with other vapour-open insulation materials of the PAVATEX range, to a healthy and breathable building.

The combination with PAVAFIX WIN sealing tape guarantees a high airtightness to the building.

Always consult the local regulations and installation guidelines of the manufacturer.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

Storage

Store the insulation boards on a flat surface, keep dry and protected from sunlight.

