

## **DECLARATION OF CONFORMITY**

N° WPBBE0503

Unique identification code of the product type: **SOPRATORCH SL 490** 

Intended use(s): Reinforced bituminous sheet for roof waterproofing

Manufacturer: Soprema NV

Bouwelven 5 - 2280 Grobbendonk

**Belgium** 

System(s) of AVCP: system 2+

Designated standard: EN 13707:2004 + A2:2009

0836 - 0086 Approved body/ies:

Declared performances

Essential characteristics			Performances		Test standard	Designated standard
External fire performance (note 1)			F <sub>ROOF</sub> (t1, t2, t3, t4)		EN 13501-5	N 13501-5
Reaction to fire			E		EN 13501-1	
Watertightness		(kPa/24 h)	≥ 10		EN 1928	
Tensile strength:	longitudinal transversal	(N/50 mm) (N/50 mm)	700 450	± 200 ± 150		
Elongation at maximum tensile strength: longitudinal transversal		(%) (%)	45 45	± 15 ± 15	EN 12311-1	
Resistance to root penetration			NPD	- 1	EN 13948	
Resistance to static loading		(kg)	≥ 15		EN 12730-A	
Resistance to impact		(mm)	≥ 1000 NPD		EN 12691-A EN 12691-B	EN 13707:2004 +
Resistance to tearing (n	nail shank)					A2:2009
7	longitudinal transversal	(N) (N)	NPD NPD		EN 12310-1	
Joint properties:	peel resistance shear resistance	(N/50 mm) (N/50 mm)	NPD 450	± 150	EN 12316-1 EN 12317-1	
Behaviour after artificial aging					EN 1296 +	
durability UV, heat and water			NPD		EN 1297	
flow resistance at elevated temperature (°C)			100	± 10	EN 1110	
flexibility at low temperature (°C)			-5	± 5	EN 1109	
Flexibility at low temperature (°C)			≤ -15		EN 1109	
Dangerous substances (note 2)			note 3		-	

NPD = no performance determined

since external fire performance depends on the other components of the roof build-up, no performance can be given this product does not contain asbestos or tar constituents

in the absence of European harmonized test methods, verification and declaration on release and content has to be done taking into account national provisions in the place of use

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with UK Regulation, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Marnix Derks, Technical Director Grobbendonk, 16/03/2023

OoC-UK-WPBBE0503.a/EN