

## AQUADERE

### Description

Cold applied solvent-free primer based on bitumen in aqueous phase.

Impregnation to ensure good adhesion to the substrate (concrete, metal and wood) before welding (torch-on or hot-air method) or gluing bituminous waterproofing membranes.

It is also suitable on old/weathered bituminous waterproofing membranes with a slate or granulate finish.

### Characteristics

Composition	bitumen in aqueous phase
Curing time *	5 min. - 3 h
Consumption (l/m <sup>2</sup> )	0,20 - 0,35
Application temperature (°C)	min. +5

\* Depending on conditions (temperature, relative humidity, layer thickness, ...)

### Packing & storage

Cans of 5 and 25 l

12 months in original unopened packaging. Store frost-free and protected from sunlight at a temperature between +5 °C and +35 °C.

### Installation

Thoroughly mix the product before use.

Apply with a brush, roller or rubber squeegee on a dry, dust- and grease free substrate.

Allow to dry completely before applying the membrane.

The tools must be free of dirt and residues of solvents as they might break the emulsion.

See label for more information.

#### Cleaning tools:

- wet product: water
- dry product: White Spirit

### Certifications



### Special indications

#### Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

#### Quality-, Environment- and Safety Management

**SOPREMA** always recognises as a high level of importance the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with

**EN ISO 9001** and **EN ISO 14001**.