



Soprema Bituminous Rolls General Information

Products

Waterproof sheeting for buildings in roll format which can be unrolled, and torch welded or adhered / self-adhered. For product-specific technical information, please read the relevant Technical Datasheet/Declaration of Performance /Environmental Product Declaration.

Storage & Handling

Soprema bituminous rolls should be stored upright, standing on end within the original packing materials. Rolls should be kept away from UV rays/heat/sparks/open flames/hot surfaces & moisture. When stored correctly, the products have an unlimited shelf life.

Rolls of products weighing more than 25kg should be handled either with mechanical handling equipment or with manual gripping tools with a load of no more than 25kg per person.

A specific pictogram is fixed to rolls weighing less than 25kg. Use suitable safe manual handling techniques.

Installation

Installation of Soprema bituminous rolls is to be carried out by Soprema Approved Installers only.

Approved Installers are to strictly follow installation instructions contained within the project specification using installation tools suitable for the project.

Installers should ensure all relevant legal and HSE requirements are complied with including but not limited to, the wearing of appropriate PPE, safe access, site securement, and work permits for hot works.

Inspection and Maintenance

Prior to the issue of the warranty, an inspection of the installation will be carried out by a Soprema Site Technician upon completion. Thereafter, the roof should be checked bi-annually, ensuring the roof is properly maintained as detailed in the specification and/or in current British Standard Codes of Practice 6229 and 8217. Records of such maintenance must be provided to Soprema via email. Details of further Soprema inspection requirements are detailed within the warranty document.

Disposal

Nature of the waste products: BIW / Banal Industrial Waste, non-hazardous waste, non-inert waste.

Waste treatment methods: At the end of a product's life, bitumen products can be disposed of with household waste and may be discharged to landfill or incinerated, subject to local regulations.

Contaminated packaging waste: the substance or mixture of waste itself and any contaminated packaging waste must be disposed of in conformance with the current local regulations at the time of disposal. Recycling and reuse of torch or adhered membranes is not possible.

Ecological information

No toxicological adverse effects on the environment are known or will ensue when used normally.

If exposed to high temperatures, the mixture may produce hazardous decomposition products, such as carbon monoxide, carbon dioxide, smoke, and nitrogen oxides.

Product Information

All versions of the documents visible on the Soprema UK website are current and valid revisions.

Historical versions or documents relating to discontinued products are available by request by emailing technical@soprema.co.uk

SOPREMA UK
Soprema House | Freebournes Road
Witham | CM8 3UN
T: +44 (0) 330 058 0668
info@soprema.co.uk
www.soprema.co.uk

VAT No. 598645471
Registered in England: 02939363