



- Long-term elastic adhesive with high adhesive strength
- Can also be used at cold temperatures
- Suitable for gluing connections on dry clean substrates

## Packaging

	Contents per container [ml/g]	Box contents [units]	Accessories included
Cartridge	310	20	20 snap-off nozzles

## Characteristics

Material	dispersion adhesive
Minimum installation temperature for base and air [°C]	frozen over, air -10
Installation temperature primer [°C]	-10 to +50
Temperature resistance [°C]	-20 to +80
Tight after [h]	depending on absorbency of substrate 2-12

## Product description

For making airtight connections of vapour-barrier and airtight membranes of all types on dry and clean substrates. The adhesive connections meet the requirements of the applicable norms DIN 4108-7, SIA 180 and ÖNORM B 8110-2.

The adhesive power is very high, with fast drying. No pressure plate is required on load-bearing substrates. The adhesive can also be used at cold temperatures.

Adhesion trials are essential for materials that are not described in the application note.

Always consult the local regulations and installation guidelines of the manufacturer.

## Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

## Storage

Shelf life: 24 months unopened

Store cool and dry, protected from sunlight.