

DECLARATION OF PERFORMANCE

n° WPLFR003

Date : June, 30th 2013

1 – Unique identification code of the product-type:

WPLFR003

2 – Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :

ALSAN 400

3 – Intended use (or uses) of the construction product :

Polyurethane resin for liquid waterproofing applications

4 – Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :

**SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG
www.soprema.com**

5 – Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :

Non applicable

6 – System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :

AVCP 3

7 – Case of the declaration of performance concerning a construction product covered by a harmonised standard :

Non applicable

8 – Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :

CSTB (Notified Body n° 0679):

- **made the determination of the product-type on the basis of type testing, according to system 3**
- **delivered the ETA-05/0007 according to ETAG 005 : 2004.**

DECLARATION OF PERFORMANCE

n° WPLFR003

Date : June, 30th 2013

9 – Declared performances :

Essential characteristics	Performances	Harmonised Technical Specification
Minimum layer thickness	1.1 mm	ETAG 005 : 2004
Factor of water vapour diffusion (μ)	≥ 650	
Resistance to wind loads	≥ 50 kPa	
External fire performance (Note 1)	F_{ROOF}	
Reaction to fire	F	
Statement on dangerous substances	No dangerous substances	
Resistance to slipperiness	NPD	
Categories of intended use according ETAG 005		
Expected working life	W2	
Climatic zone	S	
User loads	P1 (ALSAN 400 is always used under protection)	
Roof slopes	S1 to S4	
Minimum surface temperature	TL4	
Maximum surface temperature	TH2	

Note 1 : Since external fire performance depends on the other components of the roof build-up, no performance can be given.

10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.

This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

**Strasbourg,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**

