

## ALSAN PATCH

### Description

**ALSAN PATCH** is an elastic paste based on high polymers and solvents.

It has excellent adhesion to most materials, such as various roof coverings, gutters, drains and roof penetrations, without primer treatment and has excellent resistance to weathering and mineral acids.

**ALSAN PATCH** is suitable for emergency repairs in all weather conditions. It can be applied on damp surfaces.

### Characteristics

Composition	high polymers and solvents
Consumption	1 - 2,5 l/m <sup>2</sup>
Curing time	±24 h overlayable 3-14 days

### Packing & storage

Can of 1 and 5 l

Minimum 5 years, in original unopened packaging, stored in a dry and cool place, protected from the sun between +5 and +35 °C.

### Installation

**ALSAN PATCH** is applied with a spatula, brush or roller on a clean and dust-free substrate.

Do not apply on non-solvent resistant materials such as polystyrene insulation.

#### Cleaning tools:

Diluant V

### Special indications

#### Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

#### Quality-, Environment- and Safety Management

**SOPREMA** always recognises as a high level of importance the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with

**EN ISO 9001** and **EN ISO 14001**.