

ELASTOVER

ELASTOVER 36 S TSP ELASTOVER 36 S TSP KRAFT

ELASTOVER 36 S TSP and **ELASTOVER 36 S TSP KRAFT** are bitumen felts with glass fleece reinforcement, high resistance, in compliance with NF P 84-313 (36 S V.V-HR).

ELASTOVER 36 S TSP KRAFT has on its underface an independence layer made of creped kraft paper.

User application

ELASTOVER 36 S TSP can be used as vapour barrier when bitumen felt is required in compliance with NF P 84-313.

ELASTOVER 36 S TSP KRAFT is used for bridging or as thermal screen under fusible thermal insulation.

All the applications are described in **SOPREMA's** Technical Guidelines in force.

Composition

	ELASTOVER 36 S TSP	ELASTOVER 36 S TSP KRAFT
Reinforcement	Glass fleece	
Binder	Oxidized bitumen	
Nominal thickness	1,5 mm	
Weight	1,8 kg/m ²	1,7 kg/m ²
Topside	Sand	
Underside	Sand	Creped kraft paper

Packaging

	ELASTOVER 36 S TSP	ELASTOVER 36 S TSP KRAFT
Dimensions of the roll	20 m x 1 m	20 m x 1 m
Weight of the roll	about 37 kg	about 34 kg
Storage	Upright on pallet with plastic wrapping	
Roll lengths are given with a tolerance of < 1 %. Width of roll is given with a tolerance of 1% (UEAtc). Rolls must be stored upright on flat ground. During storage, protect the rolls against moisture. In cold weather, we recommend that the rolls be kept at a minimum temperature of + 2°C (+ 36 °F) for at least 5 hours before installation.		

Installation

ELASTOVER 36 S TSP is unrolled on the substrate and can be nailed on wood deck or bonded with hot bitumen.

ELASTOVER 36 S TSP KRAFT is loose laid and simply unrolled on the substrate.

Characteristics

	ELASTOVER 36 S TSP ELASTOVER 36 S TSP KRAFT	
	MDV ⁽¹⁾	MLV ⁽²⁾
Tensile properties : Tensile strength L x T (N / 50 mm) Elongation L x T (%)	400 x 400 2,8 x 2,8	350 x 300 2 x 2
Low temperature flexibility (EN 1109)	-10°C	0°C
⁽¹⁾ MDV = Manufacturer's Declared Value		
⁽²⁾ MLV = Manufacturer's Limiting Value		

Special indications

Hygiene, health and environment:

The product does not contain any substance likely to be detrimental to health or to environment and complies with generally admitted Health and Safety Requirements. For further information, please refer to relevant Safety Data Sheet.

Quality control:

SOPREMA has always attached the highest importance to the quality of its products, to the respect of environment and men.

For this reason, we apply an integrated management of the Quality and Environment certified **ISO 9001** and **ISO 14001**.