

ALSAN FLEECE P

ALSAN FLEECE P is a perforated synthetic-fibre fleece specially designed for use with ALSAN PMMA waterproofing resins. The fleece enables the layer thickness to be controlled when applying waterproofing resins and also has a strengthening and crack-bridging effect in the hardened waterproofing layer.

Material

Specific synthetic-fibre fleece with a weight per unit area of 110 g/m²

Properties

- High tear strength and tear-propagation resistance
- High elongation at break
- Specially designed for use with ALSAN PMMA's waterproofing resins in terms of material properties, thickness and degree of density
- Facilitates easy and reliable application of waterproofing with layer thickness control function

Application

ALSAN FLEECE P is used as reinforcement and to ensure a minimum layer thickness for ALSAN PMMA's waterproofing resins to create high-quality, flexible and crack-bridging waterproofing systems.

Packaging

Roll:

Width	Length
10.5 cm	50 m
15.0 cm	
20.0 cm	
26.0 cm	
35.0 cm	
52.0 cm	
70.0 cm	
105.0 cm	

Colours

ALSAN FLEECE P is white

Storage

Store **ALSAN FLEECE P** in a dry place, protected against moisture and dirt, and if possible, in a horizontal position.

Product application

A single layer of **ALSAN FLEECE P** is fully saturated with ALSAN PMMA's waterproofing resins when applied. The joints must have at least a 5 cm overlap.
For further information please refer to the product information sheets for ALSAN PMMA's waterproofing resins.

Safety information & risks

Please refer to the safety data sheet for the relevant product.

General information

The above information, in particular the product application information, is based on extensive development and many years of experience. It's provided to the best of our knowledge. However, the wide range of requirements and conditions on site means that it may be necessary for the product to be tested under those conditions to ensure that it is suitable for the intended purpose. For further information and questions, contact **SOPREMA**.

Only the most recent version of the document is valid. We reserve the right to make changes to reflect advances in technology and improvements to our products.



Marnix DERKS
Technical Director