

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: 1226e
Issue date: 23/06/2014 Revision date: 13/03/2023 Supersedes version of: 17/02/2023 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name ALSAN PMMA 072 R/ ALSAN PMMA 072 R BASE

Product code EU-SDS 1226 Product group Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SOPREMA S.A.S. 14 rue Saint Nazaire P.O. Box CS 60121 67025 STRASBOURG France

T (+33) 03 88 79 84 00 - F (+33) 03 88 79 84 01

sds@soprema.fr - www.soprema.fr

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225 Acute toxicity (oral), Category 4 H302 Skin corrosion/irritation, Category 2 H315 Skin sensitisation, Category 1 H317 Specific target organ toxicity - Single exposure, Category 3, Respiratory H335 tract irritation

Hazardous to the aquatic environment - Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Harmful if swallowed. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

Signal word (CLP) : Danger

Contains : 2-ethylhexyl acrylate (2-EHA); Methyl methacrylate; Butyl acrylate; 1,1'-(p-

tolylimino)dipropan-2-ol; 2-hydroxyethyl methacrylate

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H302 - Harmful if swallowed. H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H335 - May cause respiratory irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P321 - Specific treatment (see supplemental first aid instruction on this label).

Extra phrases : For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Methyl methacrylate substance with national workplace exposure limit(s) (IE, MT, GB); substance with a Community workplace exposure limit (Note D)	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6 REACH-no: 01-2119452498- 28	25 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
2-ethylhexyl acrylate (2-EHA) (Note D)	CAS-No.: 103-11-7 EC-No.: 203-080-7 EC Index-No.: 607-107-00-7 REACH-no: 01-2119453158- 37	25 – 50	Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
1,1'-(p-tolylimino)dipropan-2-ol	CAS-No.: 38668-48-3 EC-No.: 254-075-1 REACH-no: 01-2119980937- 17	1 – 5	Acute Tox. 2 (Oral), H300 Eye Irrit. 2, H319 Aquatic Chronic 3, H412

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Paraffin waxes and Hydrocarbon waxes substance with national workplace exposure limit(s) (IE, GB)	CAS-No.: 8002-74-2 EC-No.: 232-315-6 REACH-no: 01-2119488076- 30, 01-2119913039-42	0.1 – 1	Not classified
2-hydroxyethyl methacrylate (Note D)	CAS-No.: 868-77-9 EC-No.: 212-782-2 EC Index-No.: 607-124-00-X REACH-no: 01-2119490169- 29	0.1 – 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
toluene substance with national workplace exposure limit(s) (IE, MT, GB); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310- 51	0.1 – 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Butyl acrylate substance with national workplace exposure limit(s) (IE, MT, GB); substance with a Community workplace exposure limit (Note D)	CAS-No.: 141-32-2 EC-No.: 205-480-7 EC Index-No.: 607-062-00-3 REACH-no: 01- 211945315543	0.1 – 1	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
2,6-di-tert-butyl-4-methylphenol substance with national workplace exposure limit(s) (IE, GB)	CAS-No.: 128-37-0 EC-No.: 204-881-4 REACH-no: 01-2119480433- 40, 01-2119555270-46, 01- 2119565113-46	< 0.1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
mequinol substance with national workplace exposure limit(s) (IE)	CAS-No.: 150-76-5 EC-No.: 205-769-8 EC Index-No.: 604-044-00-7 REACH-no: 01-2119541813-	< 0.1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1, H317
methacrylic acid substance with national workplace exposure limit(s) (IE, GB) (Note D)	CAS-No.: 79-41-4 EC-No.: 201-204-4 EC Index-No.: 607-088-00-5 REACH-no: 01-2119463884- 26	< 0.1	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314 STOT SE 3, H335

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
methacrylic acid	CAS-No.: 79-41-4 EC-No.: 201-204-4 EC Index-No.: 607-088-00-5 REACH-no: 01-2119463884- 26	(1 ≤C ≤ 100) STOT SE 3, H335

Note D:

Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of H- and EUH-statements: see section 16

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a

doctor if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin

irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

13/03/2023 (Revision date) EN (English) 4/21

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective

equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be

allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Methyl methacrylate (80-62-6)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Methyl methacrylate		
50 ppm		
100 ppm		
COMMISSION DIRECTIVE 2009/161/EU		
Methyl methacrylate		
50 ppm		
100 ppm		
Chemical Agents Code of Practice 2020		
Methyl methacrylate		
50 ppm		
100 ppm		
S.L.424.24 - Chemical Agents at Work Regulations (L.N.57 of 2018)		
United Kingdom - Occupational Exposure Limits		
Methyl methacrylate		
208 mg/m³		
50 ppm		
416 mg/m³		
100 ppm		

Safety Data Sheet

Methyl methacrylate (80-62-6)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Paraffin waxes and Hydrocarbon waxes (8002-74-2)		
Ireland - Occupational Exposure Limits		
Local name	Paraffin wax, fume	
OEL TWA [1]	2 mg/m³	
OEL STEL	6 mg/m³	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
Local name	Paraffin wax	
WEL TWA (OEL TWA) [1]	2 mg/m³ fume	
WEL STEL (OEL STEL)	6 mg/m³ fume	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
toluene (108-88-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Toluene	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	384 mg/m³	
IOEL STEL [ppm]	100 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
Ireland - Occupational Exposure Limits		
Local name	Toluene	
OEL TWA [1]	192 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	384 mg/m³	
OEL STEL [ppm]	100 ppm	
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)	
Regulatory reference	Chemical Agents Code of Practice 2021	
Ireland - Biological limit values		
Local name	Toluene	
BMGV	0.02 mg/l Parameter: toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: toluene - Medium: urine - Sampling time: End of shift 0.3 mg/g creatinine Parameter: o-cresol - Medium: urine - Sampling time: End of shift - Notations: B (Background)	
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)	
Malta - Occupational Exposure Limits		
Local name	Toluene	
OEL TWA	192 mg/m³	

Safety Data Sheet

toluene (108-88-3)		
OEL TWA [ppm]	50 ppm	
OEL STEL	384 mg/m³	
OEL STEL [ppm]	100 ppm	
Remark	Skin # Ġilda	
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)	
United Kingdom - Occupational Exposure Limits		
Local name	Toluene	
WEL TWA (OEL TWA) [1]	191 mg/m³	
WEL TWA (OEL TWA) [2]	50 ppm	
WEL STEL (OEL STEL)	384 mg/m³	
WEL STEL (OEL STEL) [ppm]	100 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Butyl acrylate (141-32-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	n-Butylacrylate	
IOEL TWA	11 mg/m³	
IOEL TWA [ppm]	2 ppm	
IOEL STEL	53 mg/m³	
IOEL STEL [ppm]	10 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Ireland - Occupational Exposure Limits		
Local name	n-Butyl acrylate	
OEL TWA [1]	11 mg/m³	
OEL TWA [2]	2 ppm	
OEL STEL	53 mg/m³	
OEL STEL [ppm]	10 ppm	
Remark	IOELV (Indicative Occupational Exposure Limit Values), Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))	
Regulatory reference	Chemical Agents Code of Practice 2021	
Malta - Occupational Exposure Limits		
Local name	n-Butylacrylate	
OEL TWA	11 mg/m³	
OEL TWA [ppm]	2 ppm	

Safety Data Sheet

Butyl acrylate (141-32-2)		
OEL STEL	53 mg/m³	
OEL STEL [ppm]	10 ppm	
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)	
United Kingdom - Occupational Exposure Limits		
Local name	n-Butyl acrylate	
WEL TWA (OEL TWA) [1]	5 mg/m³	
WEL TWA (OEL TWA) [2]	1 ppm	
WEL STEL (OEL STEL)	26 mg/m³	
WEL STEL (OEL STEL) [ppm]	5 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
2,6-di-tert-butyl-4-methylphenol (128-37-0)		
Ireland - Occupational Exposure Limits		
Local name	2,6-Ditertiary-butyl-para-cresol [Butylated hydroxytoluene (BHT)]	
OEL TWA [1]	2 mg/m³	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
Local name	2,6-Di-tert-butyl-p-cresol	
WEL TWA (OEL TWA) [1]	10 mg/m³	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
methacrylic acid (79-41-4)		
Ireland - Occupational Exposure Limits		
Local name	Methacrylic acid	
OEL TWA [1]	70 mg/m³	
OEL TWA [2]	20 ppm	
OEL STEL	140 mg/m³	
OEL STEL [ppm]	40 ppm	
Regulatory reference	Chemical Agents Code of Practice 2021	
United Kingdom - Occupational Exposure Limits		
Local name	Methacrylic acid	
WEL TWA (OEL TWA) [1]	72 mg/m³	
WEL TWA (OEL TWA) [2]	20 ppm	
WEL STEL (OEL STEL)	143 mg/m³	
WEL STEL (OEL STEL) [ppm]	40 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
mequinol (150-76-5)		
Ireland - Occupational Exposure Limits		
Local name	4-Methoxyphenol [Mequinol]	
OEL TWA [1]	5 mg/m³	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

mequinol (150-76-5)

Regulatory reference

Chemical Agents Code of Practice 2021

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: LiquidColour: Colourless.Appearance: Cloudy.Odour: characteristic.Odour threshold: Not availableMelting point: Not availableFreezing point: Not available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Boiling point : > 35 °C Flammability : Not applicable **Explosive limits** : Not available : Not available Lower explosion limit Upper explosion limit : Not available 22 °C Flash point Auto-ignition temperature : Not available Decomposition temperature : Not available рΗ : Not available Viscosity, kinematic : 200 mm²/s : 200 mPa.s Viscosity, dynamic Solubility Not available : Not available Partition coefficient n-octanol/water (Log Kow) Vapour pressure Not available 159 hPa Vapour pressure at 50°C Density · 1 a/cm³ Relative density : Not available Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

ALSAN PMMA 072 R/ ALSAN PMMA 072 R BASE

ATE CLP (oral) 2000 mg/kg bodyweight

Safety Data Sheet

2-ethylhexyl acrylate (2-EHA) (103-11-7)		
LD50 oral rat	≈ 4435 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	7522 mg/kg bodyweight Animal: rabbit	
LC50 Inhalation - Rat	≥ 50 mg/l/4h	
Methyl methacrylate (80-62-6)		
LD50 oral rat	≥ 5000 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LC50 Inhalation - Rat	≥ 50 mg/l/4h	
Paraffin waxes and Hydrocarbon waxes (8002	-74-2)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
toluene (108-88-3)		
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77	
LC50 Inhalation - Rat (Vapours)	28.1 (25.7 – 30) mg/l/4h OECD 403	
Butyl acrylate (141-32-2)		
LD50 oral rat	≈ 3150 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Animal sex: male	
LC50 Inhalation - Rat (Vapours)	10.3 mg/l	
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)		
LD50 oral rat	≥ 25 (25 – 200) mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity), Guideline: other:EU Method B.3 (Acute Toxicity ((Dermal)), Guideline: other:Japan MAFF Testing Guideline of 12 Nosan No. 8147	
2,6-di-tert-butyl-4-methylphenol (128-37-0)		
LD50 oral rat	> 2930 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
methacrylic acid (79-41-4)		
LD50 oral rat	1320 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	500 – 1000 mg/kg bodyweight Animal: rabbit, Guideline: other:	
LC50 Inhalation - Rat	3.19 – 6.5 mg/l/4h OECD 403	

Safety Data Sheet

2-hydroxyethyl methacrylate (868-77-9)		
LD50 oral rat	5564 mg/kg bodyweight Animal: rat, Guideline: other:	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male	
mequinol (150-76-5)		
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: other:	
Serious eye damage/irritation :	Causes skin irritation. Not classified May cause an allergic skin reaction.	
toluene (108-88-3)		
Additional information	(OECD 406 method)	
3 ,	Not classified Not classified	
2,6-di-tert-butyl-4-methylphenol (128-37-0)		
NOAEL (chronic, oral, animal/male, 2 years)	25 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Effect type: toxicity (migrated information)	
Reproductive toxicity :	Not classified	
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)		
NOAEL (animal/male, F0/P)	40 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA, OPPTS 870.3650 (Combined Repeated dose toxicity study with the reproduction/developmental toxicity screening test)	
NOAEL (animal/female, F0/P)	20 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA, OPPTS 870.3650 (Combined Repeated dose toxicity study with the reproduction/developmental toxicity screening test)	
STOT-single exposure :	May cause respiratory irritation.	
2-ethylhexyl acrylate (2-EHA) (103-11-7)		
STOT-single exposure	May cause respiratory irritation.	
Methyl methacrylate (80-62-6)		
STOT-single exposure	May cause respiratory irritation.	
toluene (108-88-3)		
STOT-single exposure	May cause drowsiness or dizziness.	
Butyl acrylate (141-32-2)		
STOT-single exposure	May cause respiratory irritation.	
methacrylic acid (79-41-4)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure :	Not classified	
toluene (108-88-3)		
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

toluene (108-88-3)			
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
methacrylic acid (79-41-4)	methacrylic acid (79-41-4)		
LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90- Day Study)		
2-hydroxyethyl methacrylate (868-77-9)			
LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90- Day Study), Remarks on results: other:		
NOAEC (inhalation, rat, gas, 90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:		
mequinol (150-76-5)			
LOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:		
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:		
Aspiration hazard	: Not classified		
ALSAN PMMA 072 R/ ALSAN PMMA 072 R E	BASE		
Viscosity, kinematic	200 mm²/s		
Methyl methacrylate (80-62-6)			
Viscosity, kinematic	0.564 mm²/s		
Paraffin waxes and Hydrocarbon waxes (800	02-74-2)		
Viscosity, kinematic	Not applicable		
toluene (108-88-3)			
Viscosity, kinematic	≈ 0.647 mm²/s		
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)			
Viscosity, kinematic	Not applicable		
2,6-di-tert-butyl-4-methylphenol (128-37-0)			
Viscosity, kinematic	Not applicable		
methacrylic acid (79-41-4)			
Viscosity, kinematic	1.366 mm²/s		
44.0 Information on other borous			

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

Hazardous to the aquatic environment, long-term

: Harmful to aquatic life with long lasting effects.

(chronic)

Not rapidly degradable

lot rapidly degradable		
2-ethylhexyl acrylate (2-EHA) (103-11-7)		
LC50 - Fish [1]	1.81 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 - Crustacea [1]	1.3 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	1.71 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
NOEC chronic crustacea	0.19 mg/l QSAR	
NOEC chronic algae	0.45 mg/l OECD 201	
Methyl methacrylate (80-62-6)		
LC50 - Fish [1]	> 191 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
LC50 - Fish [2]	> 79 mg/l	
EC50 - Crustacea [1]	69 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	> 170 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	> 110 mg/l	
LOEC (chronic)	68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	37 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic fish	9.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'	
NOEC chronic crustacea	48 mg/l	
NOEC chronic algae	49 mg/l	
toluene (108-88-3)		
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch	
EC50 - Crustacea [1]	3.78 mg/l Ceriodaphnia dubia, 48h (US-EPA)	
EC50 72h - Algae [1]	134 mg/l freshwater algae	
ErC50 algae	134 mg/l Chlamydomonas angulosa; 3 h	
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'	
NOEC chronic crustacea	0.74 mg/l Niederlehner (1998) : 7d	
NOEC chronic algae	10 mg/l	
Butyl acrylate (141-32-2)		
EC50 96h - Algae [1]	2.65 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
NOEC chronic crustacea	0.136 mg/l (Daphnia magna, OECD 211, semi-static)	
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)		
LC50 - Fish [1]	17 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)	
	I.	

Safety Data Sheet

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
EC50 - Crustacea [1]	28.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	245 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
2,6-di-tert-butyl-4-methylphenol (128-37-0)	
LC50 - Fish [1]	0.199 mg/l
EC50 - Crustacea [1]	0.48 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	0.758 mg/l
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.023 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.053 mg/l Test organisms (species): Oryzias latipes Duration: '42 d'
methacrylic acid (79-41-4)	
LC50 - Fish [1]	85 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 130 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	45 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	20 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC chronic fish	10 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'
2-hydroxyethyl methacrylate (868-77-9)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	380 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	836 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	345 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	49.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	24.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
mequinol (150-76-5)	
LC50 - Fish [1]	28.5 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	3 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	54.7 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	19 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	1.45 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

2-ethylhexyl acrylate (2-EHA) (103-11-7)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	80 % 15d	
toluene (108-88-3)		
Biodegradation	86 % 20d	
Butyl acrylate (141-32-2)		
Persistence and degradability	Readily biodegradable.	

12.3. Bioaccumulative potential

2-ethylhexyl acrylate (2-EHA) (103-11-7)	
Bioconcentration factor (BCF REACH) 282	
toluene (108-88-3)	
BCF - Fish [1]	≈ 90 mg/kg Freitag et al (1985): 3d
Partition coefficient n-octanol/water (Log Kow)	2.73 20°C

12.4. Mobility in soil

2-ethylhexyl acrylate (2-EHA) (103-11-7)	
Surface tension 68.2 mN/m 20°C	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4.74

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IMDG IATA ADN		RID
14.1. UN number or ID n	umber			
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID	
14.2. UN proper shippin	g name				
PAINT	PAINT	Paint	PAINT	PAINT	
Fransport document descr	iption				
UN 1263 PAINT, 3, II, (D/E)	UN 1263 PAINT, 3, II (22°C c.c.)	UN 1263 Paint, 3, II	UN 1263 PAINT, 3, II	UN 1263 PAINT, 3, II	
14.3. Transport hazard	class(es)				
3	3	3	3	3	
№	3	3	3	3	
14.4. Packing group					
II	II	II	II	II	
14.5. Environmental haz	ards				
Dangerous for the environment: No environment: No Marine pollutant: No		Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No	
No supplementary information					

14.6. Special precautions for user

Special transport precautions : Single packagings ≤ 450L (ADR/ADN/RID 2.2.3.1.4, IMDG 2.3.2.2) & ≤ 30L (IATA 3.3.3.1) --

> Class 3, Packing group III

Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 163, 367, 640D, 650

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001, IBC02, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions : TP1, TP8, TP28

(ADR)

Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33

Orange plates :

33 1263

Tunnel restriction code (ADR) : D/E EAC code : •3YE

Transport by sea

Special provisions (IMDG): 163, 367Limited quantities (IMDG): 5 LExcepted quantities (IMDG): E2Packing instructions (IMDG): P001Special packing provisions (IMDG): PP1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP8, TP28

EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : B

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L

Special provisions (IATA) : A3, A72, A192

ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 163, 367, 640C, 650

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E2

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : F1

Special provisions (RID) : 163, 367, 640C, 650

Limited quantities (RID) : 5L

Excepted quantities (RID) : E2

Packing instructions (RID) : P001

Special packing provisions (RID) : PP1

Mixed packing provisions (RID) : MP19

Portable tank and bulk container instructions (RID) : T4

Portable tank and bulk container special provisions : TP1, TP8, TP28

(RID)

Tank codes for RID tanks (RID): L1.5BNTransport category (RID): 2Colis express (express parcels) (RID): CE7Hazard identification number (RID): 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

Decopaint Directive (2004/42/EC) - Annex II : A/j (Paints and Varnishes - Two-pack reactive performance coatings for specific end use

such as floors)

Maximum allowed concentration : 500 g/l VOC Maximum content of VOC : 1.66 g/l VOC

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	

13/03/2023 (Revision date) EN (English) 19/21

Safety Data Sheet

Abbreviations and acronyms:	
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:		
Acute Tox. 2 (Oral)	Acute toxicity (oral), Category 2	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H300	Fatal if swallowed.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H361d	Suspected of damaging the unborn child.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Repr. 2	Reproductive toxicity, Category 2	
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.