



- Easy installation
- Outstanding sound absorption properties

Packaging

Thickness [mm]	Boards/pallet	Dimensions [mm]	m ² /pallet [m ²]	Mass/pallet [kg]	Thermal resistance (R _d) [m ² .K/W]
32,5 (20+12,5)	25	2500 x 1200	75	1210	0,45

Characteristics insulating board

Thermal conductivity (λ_d) (EN 13171) [W/(m.K)]	0,050
Specific heat capacity (c) [J/(kg.K)]	2100
Water vapour diffusion resistance coefficient (μ) [-]	NPD
Reaction to fire (EN 13501-1)	E
Compressive strength at 10 % deformation [kPa]	≥ 100
Tensile strength perpendicular to faces [kPa]	NPD

Characteristics composed board

Mass [kg/m ³]	15,9
Edge profile	straight with bevelled longitudinal edges

NPD = no performance determined

Product description

PAVACOUSTIC 33G is a natural and ecological sound-insulation board based on wood fiber finished on one side with a 12,5 mm plasterboard.

PAVACOUSTIC 33G is mainly used as sound insulation for roofs, walls and ceilings.

The plasterboard finish with bevelled longitudinal edges makes it easy to finish.

Always consult the local regulations and installation guidelines of the manufacturer.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

Storage

Store on a flat surface, keep dry and protected from sunlight.