

**Product description:**

ALSAN FLEECE 165 P is a non-woven perforated polyester fleece specially designed for use with the ALSAN FLASHING QUADRO waterproofing resin.



**Application areas**

ALSAN FLEECE 165 P is used as reinforcement and ensures that a minimum layer thickness of the ALSAN FLASHING QUADRO waterproofing resin must be applied. The combination provides a high-quality flexible and crack-bridging waterproofing system.

**Properties**

- fleece from polyester
- improves the bridging crack
- makes it possible to check the layer thickness
- very good resistance to decomposition
- mechanically and thermally bonded

**Conditions for application**

The conditions of use depend on the resins used.

**Application:**

See technical data sheet of ALSAN FLASHING QUADRO

**Consumption**

Depending on the desired application.

**Technical characteristics**

Density: 165 g/m<sup>2</sup>

**Packing**

Width (cm)	Roll length (m)
20	50
25	50
30	50
35	50
105	50

**Storage**

Store in a dry place protected from moisture and pollution.

**Elimination**

Dispose of as construction waste, even if cured resin residues adhere to it.

**Manufactures/company**

SOPREMA SAS  
14, rue de Saint-Nazaire  
67025 Strasbourg  
France

**General information**

The information in this document is applicable to the corresponding product, provided by **SOPREMA**. Please note that this may vary from country to country. The above information, in particular the product application information, is based under normal circumstances and is provided to the best of our knowledge. The wide variety of requirements and conditions on site requires that the product must be tested under the specific conditions to ensure that it is suitable for the intended use. We reserve the right to make changes that reflect the technological progress and improvements to our products.