

AQUADERE TP

Description

Cold applied solvent-free primer based on elastomer bitumen in aqueous phase. Impregnation to ensure good adhesion to the substrate (concrete, metal and wood) before welding (torch-on method or MACADEN) bituminous waterproofing membranes from the CIVIL ROCK range. It is recommended in the waterproofing of civil engineering (for ex. bridge decks and car parks).

Characteristics

Composition	elastomer bitumen in aqueous phase
Curing time *	5 min. - 3 h
Consumption (l/m ²)	0,20 - 0,35
Application temperature (°C)	+5 / +30

* Depending on conditions (temperature, relative humidity, layer thickness, ...)

Packing & storage

Cans of 25 l

12 months in original unopened packaging. Store frost-free and protected from sunlight at a temperature between +5 °C and +35 °C.

Installation

Thoroughly mix the product before use.
Apply with a brush, roller or rubber squeegee on a dry, dust- and grease free substrate.
Allow to dry completely before applying the membrane.
The tools must be free of dirt and residues of solvents as they might break the emulsion.
See label for more information.

Cleaning tools:

- wet product: water
- dry product: White Spirit

Special indications

Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.