

DECLARATION OF PERFORMANCE

n° WPBFR204.b

Date : November, 24th 2016

1 – Unique identification code of the product-type:

WPBFR204

Commercial name (s) :

ELASTOPHENE FLAM 25

2 – Intended use(es):

**Reinforced bitumen sheets for roof waterproofing
Flexible sheets for waterproofing – bitumen damp proof sheets including bitumen
basement tanking sheets, type A**

3 – Manufacturer:

**SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG
www.soprema.com**

4 – Authorised representative:

Non applicable

5 – System(s) of assessment and verification of constancy of performance:

AVCP 2+

6a – Harmonised standard :EN 13707:2004 + A2:2009 & EN 13969:2004

Notified body(ies):

The Kiwa Polymer Institut GmbH (Notified Body n°1119):

- **performed the inspection of the system of Factory Production Control under system 2+**
- **issued the conformity certificates of Factory Production Control.**

DECLARATION OF PERFORMANCE

n° WPBFR204.b

Date : November, 24th 2016

7 – Declared performance(s) :

Essential characteristics	Performances	Harmonised Technical Specification
Classification for external fire exposure (Note 1)	F_{ROOF} (t1,t2,t3,t4)	EN 13707:2004 + A2:2009
Root resistance	NPD	
Peel resistance of joints (N / 50 mm)	NPD	
Durability Flow resistance at elevated temperature after ageing	90°C	EN 13969:2004
Durability Watertightness after ageing	Conform	
Resistance to static loading – Method B (kg)	5	EN 13707:2004 + A2:2009 EN 13969:2004
Reaction to fire	E	
Watertightness	Conform	
Resistance to impact – Method A (mm)	400	
Shear resistance of joints (N / 50 mm)	≥ 150	
Flexibility at low temperature	-16°C	
Tensile properties : Tensile strength L x T (N / 50 mm) Elongation L x T (%)	≥ 250 x 150 2 x 2	
Resistance to static loading – Method A (kg)	5	
Resistance to tearing (N)	≥ 50	
Dangerous substances (Notes 2 and 3)	Complies	

Note 1 : Since external fire performance depends on the other components of the roof build-up, no performance can be given.

Note 2 : This product does not contain asbestos or tar constituents.

Note 3 : Since there is no European test method available, no performance declaration for leaching behavior can be made. It must be made according to national rules in force in the place of use.

8 – Appropriate Technical Documentation and/or Specific Technical Documentation:

Non applicable

The performances of the product identified above is in conformity with the set of declared performance (s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by :

**Strasbourg,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**

